


Yealink Ceiling Microphone CM20 Datasheet

Beamforming Ceiling Array Microphone for Unmatched Audio Clarity



The Yealink CM20 is a premium ceiling microphone, expertly crafted to enhance audio performance in professional conference settings. Boasting an advanced array of 16 omnidirectional microphones, the CM20 captures sound in 360°, ensuring clarity and inclusivity in every discussion. With an integrated DSP, CM20 offers plug-and-play functionality with Yealink MVC systems, removing the need for external audio processing. Designed for medium to large conference rooms, the CM20 combines advanced technology with a sleek, elegant design, making it a perfect blend of functionality and style.

Key Features and Benefits

Advanced Microphone Array

CM20 is equipped with 16 omnidirectional units, providing unparalleled audio clarity across 8 independent pickup zones.

Superior Coverage

Yealink CM20 has a premium quality 30 m² full-duplex audio capture (STIPA 0.78 at a pick-up radius 3.2 meters), and effective coverage of up to 60 m² (STIPA 0.72 at a pick-up radius of 4.5 meters), in the environment of RT60=408ms @1khz, Noise Level=40dBA, 2.8-meter height, ideal for medium to large spaces.

Intelligent Sound Processing

Integrates Yealink's advanced noise reduction, echo & reverberation cancellation technologies for crystal-clear audio in every meeting.

Intelligent Tracking*

Features 8 beam outputs for precise speaker tracking and integrates with room cameras for enhanced camera tracking, enriching meeting engagement.

In-built DSP for Simplicity

Equipped with an integrated DSP, CM20 offers plug-and-play functionality with Yealink MVC systems, removing the need for external audio processing.

Network and Deployment Efficiency*

Supports AES67 for easy integration into audio networks. PoE enabled, requiring just one Ethernet cable for power and audio.

Versatile Ceiling Integration

Offers various installation options, including in-ceiling, pendant, and on-ceiling, for effortless setup and integration.

Elegant and Unobtrusive Design

Includes a removable magnetic suction mesh cover, adding a touch of sophistication while being discreet and easy to maintain.


Specifications

Parameters	Description
Package Content	<ul style="list-style-type: none"> • CM20 Microphone • White&Black Mesh Cover • Quick Start Guide • Assembly Fixing Bracket • Dust Cover • Length-Adjustable Pole (Optional) • Bracing Bridge × 1 pair • Suspend Pole Adapter (Optional) • Expansion Bolt × 6 (φ6 × 30 mm, white, Polyamide) • Self-tapping Screw × 6 (T4 × 30mm) • Machine Screw × 5 (3 × 6PMOZN3+) • Bracing Bridge Screw × 20 (M3 × 6PWMHOZN3)
Audio Specifications	<ul style="list-style-type: none"> • Frequency Response: 120Hz-16kHz • Maximum SPL: 122dB SPL • Signal Noise Ratio: 86dB @<1% THD • Sensitivity: 0 dBV/Pa 94dB SPL@1kHz • Microphone: 16 omni-direction microphone • AEC Channel: 1 channel internal
Physical Features	<ul style="list-style-type: none"> • Operating Temperature: 0-50°C • Storage Temperature: 0-70°C • Operating Humidity: 5%~90% • Typical Power: 5.7 W • Rated Power: 9 W • Interface: 1 × RJ-45 • Power Supply: PoE (IEEE 802.3af, class 3)


<p>Product Specifications</p>	<ul style="list-style-type: none"> • Size: <ul style="list-style-type: none"> ○ $\Phi 223 \times H83\text{mm}$ (with cover mesh) ○ $\Phi 215 \times H81\text{mm}$ (without cover mesh) • Weight: 615g • Product Color: Pearl Light Gray • Product Materials: ABS+PC&iron mesh • Plenum Rated UL 2043 (suitable for air handling spaces)
<p>Logistic Information</p>	<ul style="list-style-type: none"> • Box Size: $398 \times 310 \times 135\text{mm}$ • N.W/CTN: 2.462kg • G.W/CTN: 3.078kg

Polar Pattern


80Hz




125Hz




250Hz



1000Hz



2000Hz



8000Hz

